

Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) **EP 1 174 547 A1**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
23.01.2002 Bulletin 2002/04

(51) Int Cl.<sup>7</sup>: **E02F 9/28**

(21) Application number: **01202733.0**

(22) Date of filing: **17.07.2001**

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE TR**  
Designated Extension States:  
**AL LT LV MK RO SI**

(71) Applicant: **IHC HOLLAND N.V.**  
**NL-3361 EP Sliedrecht (NL)**

(72) Inventor: **Breken, Roelof**  
**4207 TD Gorinchem (NL)**


(30) Priority: **21.07.2000 NL 1015772**

(74) Representative: **Lips, Hendrik Jan George, Ir.**  
**HAAGSCH OCTROOIBUREAU Breitnerlaan 146**  
**2596 HG Den Haag (NL)**

(54) **Assembly of a tooth and an adapter for an excavator, such as a cutter or the like**

(57) Assembly of a tooth (3) and an adapter (1) for application with an excavator, such as e.g. a cutter. The parts have telescoping elements (4 and 2, respectively) with tapering surfaces. Recesses (11, 12) for receiving a locking element (10) are made in two abutting surfaces. At least one of said two abutting surfaces (5, 7) of the tooth (3) and/or the adapter (1) has a curved surface

as seen transverse to the sliding direction of the parts. Both abutting surfaces (5, 7) can be of curved design with the centres (6, 8, resp.) of the radii of curvature (R, S, resp.) are at the same side of the abutting surfaces and one radius of curvature (S) being larger than the other (R) so that initially the surfaces contact each other according to a line (9).



EP 1 174 547 A1

**BEST AVAILABLE COPY**

## Description

[0001] The invention relates to an assembly of a tooth and an adapter for application with an excavator, such as a cutter or the like, in which the tooth and the adapter have telescoping elements with substantially tapering surfaces and recesses for receiving a locking element are mounted in two contacting surfaces of said elements.

[0002] Such an assembly is known from EP-B-0182357 and is aimed at making it possible to replace a worn or damaged tooth instead of an entire cutter or similar machine part. With said assembly, the planes of the mating elements are in abutment across almost their entire surfaces. This entails that narrow dimensional tolerances should be maintained in order to achieve that the tooth projects beyond the adapter across the desired distance. However, it is desirable that on manufacturing those parts, they require no final processing, or one as small as possible. The parts concerned are generally manufactured by casting or forging.

[0003] If e.g. the cavity in the part to be slid on has a dimension which is slightly too small, sliding will cause difficulties because large frictional forces between the abutting planes will occur. In case of a dimension which is too large, one will not achieve a tight connection between the tooth and the adapter. In both cases, the tooth will possibly not be in the desired position and thus be less effective.

[0004] The object of the invention is to remove these difficulties and to that end provides for, that at least one of two abutting planes of the tooth and/or the adapter has a curved surface as seen in the direction transverse to the sliding direction of the parts.

[0005] With telescoping the parts, now only certain parts of the abutting planes should be pushed away slightly. Due to this, the desired position of the parts in relation to each other can be achieved more easily. It has turned out that the curved surfaces of one part are slightly deformed elastically on telescoping the parts and adapt to the abutting surfaces of the other part. The frictional forces occurring during sliding-in, will be considerably lower than when the surfaces abut across their entire widths, as is the case with the known assembly.

[0006] Nevertheless, it has been shown possible to achieve a very tight connection between the parts. Further, calculation has shown that on applying the invention a better contact of the surfaces is achieved and that the occurring tensions are lower than with the known assembly.

[0007] In particular, it can be provided for, that both abutting surfaces are designed with a curvature, in such a way that the centres of the radii of curvature of both parts are at the same side of the abutting surfaces and one radius of curvature is larger than the other, in such a way that initially the surfaces contact each other only according to a line.

[0008] Obviously, it is also possible to provide only

one of the two abutting walls with a curvature, so that likewise initially the walls will contact each other according to a line. All abutting walls of the parts can be provided with a curvature, but obviously this is not absolutely necessary.

[0009] When the assembly is executed in such a way, that the tooth has a pocket and is slid onto the adapter, the latter can be provided with wedge-shaped cams to facilitate removing a tooth from the adapter.

[0010] Further, the adapter can be provided with cams for indicating the position where the tooth must be located on the adapter. Then, the tooth can be prevented from being slid onto the adapter too far.

[0011] With the known assembly, a bent thread of spring steel is employed as locking element. This has the difficulty, that the locking element only locally abuts the walls of the recesses in the surfaces concerned of the tooth and the adapter. Due to the open shape of the element, during operation of the device, sand and clay will collect and solidify there, even if the element will often be located largely under water. Removal of the element afterwards with replacement of a tooth may then cause difficulties. Namely, the element must be compressed slightly in order to be able to pass the relative small openings above or below the recess.

[0012] In this aspect too, the present invention intends to provide an improvement, in that the locking element is assembled from two substantially L-shaped strips, with one set of legs thereof extending in parallel and being spaced apart with interposition of an elastic body, and the other legs fall around said elastic body and that in such a way that one leg lies on the other.

[0013] The mutually parallel legs of the strips largely abut the walls of the recesses in the tooth and the adapter. Since at the other side the legs abut the elastic body, they can be pressed towards one another to a degree sufficiently for moving the locking element into the recesses intended for it. At both sides of the recesses, into which the locking element should fall, there are narrow holes through which the locking element should be pushed when it is to be brought into the recesses. The holes are narrow so that the locking element can not be removed from the recesses in an uncontrolled way.

[0014] On bringing the locking element into the recesses, one operates in such a way, that the free ends of the parallel legs of the strips are pressed towards one another in order to be brought into a hole. After that, the upper leg of the one strip can be hit upon in order to move the locking element further inwards. Owing to the fact that said leg, which is hit upon, bears on the leg of the other strip, both strips are moved inwards simultaneously, so that no shearing forces will be exerted on said elastic body.

[0015] For bringing the locking element into the recesses with ease, the free ends of the parallel legs of the strips will be bent in such a way, that across a certain distance they will lie closer to one another than where the major portion of the elastic body is located. Then,

after mounting of the locking element, the parts being closer together will be pressed against the edges of the hole situated adjacent the recesses.

[0016] Enclosing of the locking element in the recesses can be improved in that the leg of the other strip lying on the leg of the one strip, through a bent portion, will continue into the other leg of the same strip. Said bent portion of the strip of the locking element will provide for that this strip will leave the hole positively when the locking element has largely passed the hole. The strip will then be pressed against the wall of the recess by the elastic element so that the locking element will no longer be able to perform a return movement.

[0017] When the locking element should be removed from the recesses, for the purpose of replacing a tooth, a tool can hit on the same leg as with insertion of the locking element. Then, likewise no shearing forces will be exerted on the elastic body.

[0018] The invention is further explained by way of an example, illustrated in the drawing, in which:

Fig. 1 shows schematically a plan view of the assembly according to the invention;

Fig. 2 shows schematically a cross-section according to the line II-II in Figure 1;

Fig. 3 shows schematically a cross-section according to the line III-III in Figure 2;

Fig. 4b shows schematically a cross-section according to the line IV-IV in Figure 1;

Fig. 5 shows schematically a part of Figure 4 on a highly enlarged scale;

Fig. 6 shows a lateral view, on an enlarged scale, of the locking element applied with the assembly according to the Figures 1-5; and

Fig. 7 shows a cross-section according to the line VII-VII in Figure 6.

[0019] The assembly illustrated in the Figures comprises the adapter 1 provided with a receiving portion 2 and a tooth 3 mounted on it, to that end being provided with a cavity 4. In a way not further indicated, the adapter 1 is releasably or otherwise connected to a part of the excavating machine, such as a cutter, for example.

[0020] As appears in particular from Figures 1-3, the abutting walls of the receiving part 2 and of cavity 4 are tapered towards one another in longitudinal direction of the parts 1 and 3.

[0021] Figure 4 shows a cross-section across the receiving part 2 and the tooth 3 where the cavity 4 in the tooth 3 is located. As appears from Fig. 5 in particular, the wall 5 of the cavity 4 has a curved shape, with the centre 6 of the radius of curvature R being located at a considerable distance from the wall 5. Wall 7, located opposite the wall 5, of receiving part 2 has a radius of curvature S being slightly larger than R and having its centre indicated by 8. Walls 5 and 7 will basically contact one another according to the line 9 at the beginning of telescoping of the parts. On telescoping further, the

parts located adjacent the line 9 will also contact each other as a result of elastic deformation. The parts being located adjacent the line 9 need only have a limited width in order to have a sufficiently high enclosing force between the parts. Due to that, the friction between the parts will remain limited, so that sliding-in can take place relatively easy.

[0022] A locking element 10 is employed for guaranteeing a positive enclosure of the parts in relation to one another. At one side, the element 10 abuts the wall of a recess 11 in the receiving part 2 and at the other side it abuts a wall of a recess 12 in the tooth 3, at the position of the cavity 4 in it.

[0023] As appears from Figures 6 and 7 in particular, the locking element is formed by two L-shaped strips 13 and 14 having their legs 15 and 16 respectively extending in parallel and being connected to one another by an elastic body 17, consisting of rubber or a similar material, for example. The legs 15 and 16 of the strips can be provided with ribs 18, see Figure 7, for establishing a firm connection between the strips and the elastic body 17. With a bent part 19, leg 15 of the strip 13 passes into the leg 20, abutting the outer side of the leg 21 of the strip 14. The free ends of the legs 15 and 16 are provided with flanged parts for forming two parts 22 being closer together. After sliding the locking element 10 into the recesses 11 and 12, parts 22, under compression of the elastic body 17, will abut the receding walls of a hole 23 situated below the recesses, as appears from Figure 2 in particular.

[0024] Above the recesses 11 and 12, there is also a hole 23, and both holes have smaller dimensions than the recesses. As stated above, the locking element 10 will be pushed through the uppermost hole 23 as seen in Figures 2 and 4, in which a hammer can be employed for exerting a force K, as indicated in Fig. 2. On removing the locking element from the recesses, a force in the same direction will be exerted on the locking element.

[0025] As appears from Figure 1 in particular, the adapter 1 can be provided with wedge-shaped cams 24 for removing a tooth 3 from the adapter.

[0026] Removing the tooth from the adapter can take place by hitting on the back side of the tooth, namely alternately on its various edges. However, when the cams 24 are present, a two-teeth wedge-shaped fork can be driven between these cams and the back side of the tooth in order to release the tooth from the adapter. In most cases, this makes releasing the tooth easier and less time-consuming.

[0027] It is also possible to apply cams 25 for preventing a tooth from being slid onto the adapter too far and for checking if the tooth is located in the appropriate position.

[0028] When a tooth would be slid onto the adapter too far, the material of the tooth might get overstretched. The tooth would then be clamped onto the adapter too tightly and get under high tension. This might lead to premature failure of the tooth due to cracks or to prema-

ture failure of the adapter due to clamping forces.

[0029] It will be obvious, that only one possible embodiment of an assembly according to the invention has been illustrated in the drawing and explained in the description and that many changes can be made without leaving the inventive idea as it has been described in the claims.

another than where the major portion of the elastic body (17) is located.

7. Locking element according to claim 5 or 6, **characterized in that** the leg (20) of the other strip (13) lying on the leg (21) of the one strip (14), through a bent portion (19), will pass into the other leg (15) of the same strip (13).

#### Claims

1. Assembly of a tooth (3) and an adapter (1) for application with an excavator, such as e.g. a cutter in which the tooth and the adapter have telescoping elements (4 and 2, respectively) with substantially tapering surfaces and recesses (11, 12) for receiving a locking element (10) are mounted in two contacting surfaces of said elements, **characterized in that** at least one of two abutting surfaces (5, 7) of the tooth (3) and/or the adapter (1) has a curved surface as seen in the direction transverse to the sliding direction of the parts.
2. Assembly according to claim 1, **characterized in that** both abutting surfaces (5, 7) are designed with a curvature, in such a way that the centres (6, 8, resp.) of the radii of curvature (R, S, resp.) of both parts (4, 2, resp.) are at the same side of the abutting surfaces and one radius of curvature (S) is larger than the other (R), in such a way that initially the surfaces contact each other only according to a line (9).
3. Assembly according to claim 1 or 2, **characterized in that** the tooth (3) has a pocket (4) and is slid onto the adapter (1), **characterized in that** the adapter (1) is provided with wedge-shaped cams (24) to facilitate removing a tooth from the adapter.
4. Assembly according to claim 3, **characterized in that** the adapter (1) is provided with cams (25) for indicating the position where the tooth must be located on the adapter.
5. Locking element for application with the assembly according to one of the preceding claims, **characterized in that** the locking element (10) is assembled from two substantially L-shaped strips (13, 14), with one set of legs (15, 16) thereof extending in parallel and being spaced apart with interposition of an elastic body (17), and the other legs (20, 21) fall around said elastic body and that in such a way that one leg (20) lies on the other (21).
6. Locking element according to claim 5, **characterized in that** the free ends of the parallel legs (15, 16) of the strips (13, 14) are bent in such a way, that across a certain distance they will lie closer to one

FIG. 1




FIG. 2




FIG. 4




FIG. 3




FIG. 5




FIG. 6





FIG. 7



BEST AVAILABLE COPY



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 01 20 2733

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 3 444 633 A (HENSLEY RUSTON C) 20 May 1969 (1969-05-20)	1	E02F9/28
A	* figures 2-10 * * column 2, line 23 - column 3, line 2 *	2	
X	US 2 050 014 A (MORRISON) 4 August 1936 (1936-08-04)	1	
A	* figures * * page 1, right-hand column, line 7 - line 33 *	2	
X	US 4 835 888 A (HEMPHILL CHARLES W) 6 June 1989 (1989-06-06)	1	
A	* figures 4-13 * * column 4, line 18 - line 30 *	2,5	
X	US 4 251 933 A (HEMPHILL CHARLES W) 24 February 1981 (1981-02-24)	1	E02F
A	* figures 11-14 *	2	
X	FR 2 032 575 A (VILLECHENON LOUIS) 27 November 1970 (1970-11-27)	1	
A	* claims; figures *	2	
X	EP 0 835 963 A (DOS ASESORAMIENTO Y GESTION S) 15 April 1998 (1998-04-15)	1	
A	* figure 12 * * column 3, line 50 - column 4, line 25 *	2	
X	US 5 778 570 A (EICHELBERGER PETER) 14 July 1998 (1998-07-14)	1	
A	* figures 3-5,7 * * column 2, line 55 - line 65 *	2	
X	US 5 956 874 A (IANELLO GARRICK J ET AL) 28 September 1999 (1999-09-28)	1	
A	* figures 1,5 *	2	
		-/--	
The present search report has been drawn up for all claims			
Place of search <b>THE HAGUE</b>		Date of completion of the search <b>12 October 2001</b>	Examiner <b>Guthmuller, J</b>
CATEGORY OF CITED DOCUMENTS		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document			

EPO FORM 1503 03/02 (p04001)



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 01 20 2733

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	FR 2 545 122 A (LIEBHERR FRANCE) 2 November 1984 (1984-11-02)	1	
A	* figures 3,4,6 * * page 5, line 6 - line 20 *	2	
X	US 3 601 911 A (WOOD DONALD L) 31 August 1971 (1971-08-31)	1	
A	* column 2, line 13 - line 45 * * figures 2,4 *	2	
X	LU 67 039 A (COCHET) 19 April 1973 (1973-04-19)	1	
A	* figures *	2	
X	US 4 823 487 A (ROBINSON HOWARD W) 25 April 1989 (1989-04-25)	1	
A	* figure 5 *	2	
A	FR 2 175 120 A (BOFORS AB) 19 October 1973 (1973-10-19)	5-7	
	* figures * * page 2, line 1 - line 7 *		
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
Place of search <b>THE HAGUE</b>		Date of completion of the search <b>12 October 2001</b>	Examiner <b>Guthmuller, J</b>
<p><b>CATEGORY OF CITED DOCUMENTS</b></p> <p>X : particularly relevant if taken alone  Y : particularly relevant if combined with another document of the same category  A : technological background  O : non-written disclosure  P : intermediate document</p> <p>T : theory or principle underlying the invention  E : earlier patent document, but published on, or after the filing date  D : document cited in the application  L : document cited for other reasons  &amp; : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 20 2733

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

12-10-2001

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
US 3444633	A	20-05-1969	NONE		
US 2050014	A	04-08-1936	NONE		
US 4835888	A	06-06-1989	NONE		
US 4251933	A	24-02-1981	NONE		
FR 2032575	A	27-11-1970	FR	2032575 A5	27-11-1970
			DE	2022931 A1	13-05-1971
EP 0835963	A	15-04-1998	EP	0835963 A1	15-04-1998
			AT	184670 T	15-10-1999
			AU	719442 B2	11-05-2000
			AU	2839197 A	15-01-1998
			BR	9703813 A	03-11-1998
			DE	69604293 D1	21-10-1999
			DE	69604293 T2	23-03-2000
			ES	2138311 T3	01-01-2000
			JP	10102548 A	21-04-1998
			US	5918391 A	06-07-1999
US 5778570	A	14-07-1998	CA	2163164 A1	18-05-1997
			AT	136968 T	15-05-1996
			DE	59400217 D1	23-05-1996
			EP	0649945 A1	26-04-1995
			ES	2088698 T3	16-08-1996
US 5956874	A	28-09-1999	AU	2698399 A	18-11-1999
FR 2545122	A	02-11-1984	DE	3315024 A1	31-10-1984
			FR	2545122 A1	02-11-1984
US 3601911	A	31-08-1971	NONE		
LU 67039	A	19-04-1973	FR	2171989 A1	28-09-1973
			BE	795376 A1	29-05-1973
			DE	2308296 A1	23-08-1973
			IT	976724 B	10-09-1974
			JP	48094202 A	05-12-1973
			LU	67039 A1	19-04-1973
			NL	7302180 A	21-08-1973
US 4823487	A	25-04-1989	CA	1282812 A1	09-04-1991
FR 2175120	A	19-10-1973	DE	7304417 U	17-05-1973

EPO FORM P459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82



EP 01 20 2733

12-10-2001

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
FR 2175120 A	ES FR	189146 Y 2175120 A1	01-10-1974 19-10-1973
-----			

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82